




PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	1/6

FINISHES & MATERIAL SPECIFICATION SHEET

Item Description	Acoustic Operable Wall System	  
Model Type	'flexifold' type F100 Solid Manual	
Dimensions	Standard panel thickness - 100mm nominal Refer to Corresponding Drawings	
External Frame	6063-T5 Aluminium Extrusion	
Finish	Natural anodized finish	
Support Frame	Construction Steel	
Corner Seal	Foam	
Sound Seal	E.P.D.M. Strip	
Facing Panel	A large selection of finishes, ranging from wood, fabrics to steel, with glass window inserts are available.	
Panels Size	Each panel shall be of height (Max. 4.5 M.) and width to suit each specific location. Contractor shall propose the actual panel size for architect's approval.	
Supplier	Flexifold International China Ltd.	
Address	Rm 1501 Kwong Kin Trade Centre, 5 Kin Fat Street, Tuen Mun, N.T., HK	
Contact	Tel : 852 2448 1807 Fax : 852 2448 0473 email : info@flexifoldhk.com Web Site : www.flexifoldhk.com	


PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	2/6

FINISHES & MATERIAL SPECIFICATION SHEET

Track System - Type 'B'

Overhead track channel system shall be 'Flexifold' type B aluminium track formed of metal plate rigid enough to limit deflection to 1mm or less from the operation of the wall panels.


It is of paramount importance that the sound baffle wall surrounding the track and above the operable wall panels be properly sealed and constructed to prevent flanking transmission of noise. It shall be the responsibility of the Contractor supplying and installing these operable walls to provide details of the bulkhead for comments and approval by the Architect or his designated Consultant prior to actual construction.




Carriage System Materials and Specifications Table

Model Type	Name	Materials & Model No.	Load Computation (Unit)	Remarks
B-Track System (Partition Height From 1.8 to 6 Meters / Panel Weight up to 350kg Max.)	Aluminium Track	6mm Thick Aluminium Extrusion (6063-T6)	65MPa	Surface finishing is standard white PVF II
	Type B Connection Joint	Stainless Steel #304 Precise Die-casting	250MPa	Surface finishing is standard white PVF II
	Type B Multi-Directional Roller	φ40mm Steel Bearing (Model No.: 6203)	9.6kN (Load Ratings Dynamic)	Each roller contain 4 steel bearings
			4.6kN (Load Ratings Static)	
Hanger Rod	M12 High Tensile Hanger Rod	350MPa	Two Points Suspension	

T- Joint






L - Joint



PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	3/6

FINISHES & MATERIAL SPECIFICATION SHEET

Normal Panel - F100 Solid Manual






Typical Cross Section A - A

Panels units shall be Flexifold Type F100 model, manually and individual operated. Each panel should be top supported by ball bearing swivel trolleys. There shall be no track or guide in or on the floor. The entire panel shall be incombustible, moisture resistant and dimensionally stable, the panel support system shall include a fail-safe device which prevents locating or tracking out after the panels have be installed. Each panel shall have vertical seals between panels and should consist of tongue and groove configuration with effective acoustic magnetic strip seals. Horizontal top and / or bottom seals shall be adjustable to cater to dimensional variation in height. Individual floor seals on the bottom of each panel should provide 20mm minimum nomial operation clearance and should be manually crank operated from the edge of the panel. Downward seal pressure MUST ensure an acoustical seal and resist lateral panel movement satisfactory.

PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	4/6

FINISHES & MATERIAL SPECIFICATION SHEET

Telescopic End Panel - F100 Solid Manual



Telescopic End Section B - B

In order to maintain the acoustic integrity and absorb the discrepancies of length dimension as well as vertical level on site, telescopic end panel is designed to permit extensions (gap fillers) in three directions. The outward pushing stroke of the ceiling and floor contact sections should be standardized at 20mm, and the telescopic section can be adjusted from 100mm to 120mm by means of internal mechanism extending / retracting sound seals.

PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	5/6


FINISHES & MATERIAL SPECIFICATION SHEET

Panel With Single Passdoor - F100 Solid Manual


Upon the requirements of uniform design and beauty, single passdoor or double passdoor are provided by flexifold to fulfill this criterion.

It can resist impact forces as caused by opening, closing, pushing and stacking of elements.

The doors are equipped with heavy duty stainless steel hinges, handles, base plate and locking mechanism with master keys.



Typical Cross Section A A



Passdoor B - B

PROJECT		MODEL	F100 SOLID	DATE	PAGE
LOCATION		TYPE	MANUAL	21-Jul-14	6/6

FINISHES & MATERIAL SPECIFICATION SHEET

Acoustic Performance

The OPERABLE WALL shall have an STC/SRI rating from **Laboratory Testing of 51 ~ 53** AND PROVIDE AND **STC / SRI 42 ~ 45 IN-PLACE** with noise control measurements taken at 1.25m from panel face at standing and sealed 'ear' level along the length of the wall, allowing from room effect.

In order to meet these noise criteria successfully normally requires that the panels be a minimum of **100mm thick**. Surface density shall be minimum **70kg/m²** (without surface finishing/treatment).

Each panel constructed of torsion-free aluminium/steel frame, cladding with **15mm thick MDF board** covered with galvanized steel sheet gauge 20 + 7mm thick gypsum board back up to both sides.

It shall be the responsibility of the Contractor to demonstrate (by carry out site acoustic tests) the noise control ability of the operable walls. The acoustics tests shall be witnessed by the Architect's or his designated Consultant. The Contractor shall submit details of the proposed test method for the Architect's approval prior to conducting this test. Formal test report shall be issued to the Architect within two weeks after the acoustic test.

Guarantee

The operable wall system shall be GUARANTEED in writing against defective workmanship and material for FIVE YEARS from date of completion. The form of guarantee should include the overhead carriage system (roller and aluminium / steel track) and panels which should further include all internal mechanisms as well as all ironmongeries.